
State Contraction of the state	

		0		(1	- r	5	(C	2	1	1	$ \mathbf{O} $		U	TQG	
		SIZE		MAX.	LOAD	R	IM	SECTIO	N WIDTH	OVERALL	DIAMETER	TREAD	DEPTH	SLR.	S/W			
				lbs	kgs	MEASURING	APPROVED	mm	inch	mm	inch	mm	/32″	mm		TREAD.	TRAC. T	EMP.
20	***	275/ 40R 2	D 106 Y	2094	950	9.5	9.0 ~ 11.0	278	10.9	728	28.7	7.9	10/32	340	BSW	-	-	-
inch	***	255/ 45R 2	D 101 W	1819	825	8.5	8.0 ~ 9.5	255	10.0	738	29.1	7.9	10/32	344	BSW	-	-	-
	**	235/ 45R 1	9 95 W	1521	690	8.0	7.5 ~ 9.0	236	9.3	695	27.4	7.9	10/32	325	BSW	-	-	-
	**	255/ 45R 1	9 100 V	1764	800	8.5	8.0 ~ 9.5	255	10.0	713	28.1	7.9	10/32	332	BSW	-	-	-
19	**	285/ 45R 1	9 107 W	2149	975	9.5	9.0 ~ 10.5	285	11.2	739	29.1	7.9	10/32	342	BSW	-	-	-
inch	**	235/ 50R 1	9 99 V	1709	775	7.5	6.5 ~ 8.5	245	9.6	719	28.3	7.9	10/32	334	BSW	-	-	-
	**	255/ 50R 1	9 103 W	1929	875	8.0	7.0 ~ 9.0	265	10.4	739	29.1	7.9	10/32	342	BSW	-	-	-
	**	235/ 55R 1	9 105 V	2039	925	7.5	6.5 ~ 8.5	245	9.6	741	29.2	7.9	10/32	343	BSW	-	-	-
	**	235/ 45R 1	B 98 W	1653	750	8.0	7.5 ~ 9.0	236	9.3	669	26.3	7.9	10/32	312	BSW	-	-	-
10	**	285/ 50R 1	B 109 W	2271	1030	9.0	8.0 ~ 10.0	297	11.7	743	29.3	7.9	10/32	341	BSW	-	-	-
18 inch	*	255/ 55R 1	B 109 W	2271	1030	8.0	7.0 ~ 9.0	265	10.4	737	29.0	7.9	10/32	338	BSW	-	-	-
	***	225/ 60R 1	B 100 W	1764	800	6.5	6.0 ~ 5.0	228	9.0	727	28.6	7.9	10/32	334	BSW	-	-	-
	**	235/ 60R 1	B 103 V	1929	875	7.0	6.5 ~ 8.5	240	9.4	739	29.1	7.9	10/32	339	BSW	-	-	-
47	**	225/ 50R 1	7 98 W	1653	750	7.0	6.0 ~ 8.0	233	9.2	658	25.9	7.9	10/32	305	BSW	-	-	-
17 inch	***	255/ 60R 1	7 106 V	2094	950	7.5	7.0 ~ 9.0	260	10.2	738	29.1	7.9	10/32	336	BSW	-	-	-
	**	235/ 65R 1	7 108 V	2205	1000	7.0	$6.5 \sim 8.5$	240	9.4	738	29.1	7.9	10/32	336	BSW	-	-	-

% These data can be changed by the manufacturer without prior notice, and differently applied by regions.
* Available at the 1st Quarter of 2013, ** Available at the 2nd Quarter of 2013, *** Available at the 3rd Quarter of 2013





NEXENTIRE www.nexentire.com

SALES HEADQUARTER 3FL. NEXEN BLDG. 796-27 BANGBAE-DONG SEOCHO-GU, 137-060, SEOUL, KOREA T +82-2-3476-2782 F +82-2-3476-2205~6

N'FERA RU1 255/55R18 EU Labelling class * EU lable classes will continue to be updated. Please visit our website regularly.



Fantastic Driving

With a fantastic ride and superb steering, your driving experience will be raised to the next level



Superb driving experience

As a premium tire fitted out with new technologies for the best SUV driving experience, **N** FERA RU1 provides superb handling and grip.

Wet Grip

4G optimized compound technology delivers an optimized tread grip on both wet and dry surfaces.

Handling Improved block stiffness and balanced construction provides excellent handling and steering stability.


Ride Comfort & Long mileage Special tread compound, lexible sidewall and optimi

asymmetric pattern design delivers a refreshing ride comfort & long mileage

Performance Test Results


Wet Grip





Dry Handling







Wet Grip and


Dry Handling with

* FOS : Footprint Optimum-shape Simulation

Perfect Balance and Stability

Comfort





Performance Index (%)

Provide Best Comfort

N'Fera RU1's POS technology and pattern design delivers a more comfortable drive.

Pattern Design

Three Wide Grooves



Three wide grooves on the in-side part that wields great influence upon the driving performance in the rain are applied to improve hydro/wet performance


One Narrow Groove



One narrow groove on outside is applied to increase the block stiffness and thereby improve handling and steering stability during cornering




Performance Radar Charts






Provides excellent wet/dry grip

save fuel









Optimized Out/In Rib Balance

Optimized out/in rib balance delivers the best stability during high-speed driving



Silent Sipes

Silent sipes disperse noise from high stiffness block and, consequently, have a very low noise output



N*FERARU1* provides superior braking on wet surfaces and superb handling in the dry realizing an unmatched ride that could not be felt through any other SUV tires.



Net	
ning	

_	N FERA RUI
	Competitor A
	Competitor B
	Conventional


- * Test Size : 255/55R18 109W
- * Test Site : Spain Idiada Applus P/G
 - STL (Standards Testing Labs, USA)
 - LPG (Laredo Providing Grounds. Ltd, USA)
 - TUV (TUV SUD Automotive, Germany)
- * Test vehicle : Volkswagen Touareg



			O SIZE		МАХ. I			≓ ™	SECTION		OVERALL		1 TREAD	<u>∫∏</u> DEPTH	OI SLR.	S/W	U	rqg	
			SIZE		lbs	kgs	MEASURING	APPROVED	mm	inch	mm	inch	mm	/32″	mm		TREAD.	TRAC. T	TEMP.
20	***	275/	40R 20	106 Y	2094	950	9.5	9.0 ~ 11.0	278	10.9	728	28.7	7.9	10/32	340	BSW	-	-	-
inch	***	255/	45R 20	101 W	1819	825	8.5	8.0 ~ 9.5	255	10.0	738	29.1	7.9	10/32	344	BSW	-	-	-
	**	235/	45R 19	95 W	1521	690	8.0	$7.5 \sim 9.0$	236	9.3	695	27.4	7.9	10/32	325	BSW	-	-	-
	**	255/	45R 19	100 V	1764	800	8.5	$8.0 \sim 9.5$	255	10.0	713	28.1	7.9	10/32	332	BSW	-	-	-
19	**	285/	45R 19	107 W	2149	975	9.5	9.0 ~ 10.5	285	11.2	739	29.1	7.9	10/32	342	BSW	-	-	-
inch	**	235/	50R 19	99 V	1709	775	7.5	$6.5 \sim 8.5$	245	9.6	719	28.3	7.9	10/32	334	BSW	-	-	-
	**	255/	50R 19	103 W	1929	875	8.0	7.0~9.0	265	10.4	739	29.1	7.9	10/32	342	BSW	-	-	-
	**	235/	55R 19	105 V	2039	925	7.5	$6.5 \sim 8.5$	245	9.6	741	29.2	7.9	10/32	343	BSW	-	-	-
	**	235/	45R 18	98 W	1653	750	8.0	7.5 ~ 9.0	236	9.3	669	26.3	7.9	10/32	312	BSW	-	-	-
4.0	**	285/	50R 18	109 W	2271	1030	9.0	8.0 ~ 10.0	297	11.7	743	29.3	7.9	10/32	341	BSW	-	-	-
18 inch	*	255/	55R 18	109 W	2271	1030	8.0	7.0~9.0	265	10.4	737	29.0	7.9	10/32	338	BSW	-	-	-
	***	225/	60R 18	100 W	1764	800	6.5	$6.0 \sim 5.0$	228	9.0	727	28.6	7.9	10/32	334	BSW	-	-	-
	**	235/	60R 18	103 V	1929	875	7.0	6.5 ~ 8.5	240	9.4	739	29.1	7.9	10/32	339	BSW	-	-	-
4.7	**	225/	50R 17	98 W	1653	750	7.0	6.0 ~ 8.0	233	9.2	658	25.9	7.9	10/32	305	BSW	-	-	-
17 inch	***	255/	60R 17	106 V	2094	950	7.5	7.0~9.0	260	10.2	738	29.1	7.9	10/32	336	BSW	-	-	-
mon	**	235/	65R 17	108 V	2205	1000	7.0	6.5 ~ 8.5	240	9.4	738	29.1	7.9	10/32	336	BSW	-	-	-

% These data can be changed by the manufacturer without prior notice, and differently applied by regions.
* Available at the 1st Quarter of 2013, ** Available at the 2nd Quarter of 2013, *** Available at the 3rd Quarter of 2013





SALES HEADQUARTER 3FL. NEXEN BLDG. 796-27 BANGBAE-DONG SEOCHO-GU, 137-060, SEOUL, KOREA T +82-2-3476-2782 F +82-2-3476-2205~6 N'FERA RU1 255/55R18 EU Labelling class ** EU lable classes will continue to be updated. Please visit our website regularly.



Fantastic Driving

With a fantastic ride and superb steering, your driving experience will be raised to the next level



Superb driving experience

As a premium tire fitted out with new technologies for the best SUV driving experience, **N** FERA RU1 provides superb handling and grip.

Wet Grip

4G optimized compound technology delivers an optimized tread grip on both wet and dry surfaces.

Handling Improved block stiffness and balanced construction provides excellent handling and steering stability.


Ride Comfort & Long mileage

flexible sidewall and optim asymmetric pattern design delivers a refreshing ride comfort & long mileage

Performance Test Results


Wet Grip





Dry Handling







Wet Grip and

Dry Handling with

* FOS : Footprint Optimum-shape Simulation

Perfect Balance and Stability

Comfort





Performance Index (%)

Provide Best Comfort

N'Fera RU1's POS technology and pattern design delivers a more comfortable drive.

Pattern Design

Three Wide Grooves




Three wide grooves on the in-side part that wields great influence upon the driving performance in the rain are applied to improve hydro/wet


One Narrow Groove



One narrow groove on outside is applied to increase the block stiffness and thereby improve handling and steering stability during cornering




Performance Radar Charts






 Improved durability ·Enhanced stability with better handling and steering response Increased treadwear •Minimized rolling resistance to save fuel Provides excellent wet/dry grip







Optimized Out/In Rib Balance



Optimized out/in rib balance delivers the best stability during high-speed driving



Silent Sipes

Silent sipes disperse noise from high stiffness block and, consequently, have a very low noise output



N*FERARU1* provides superior braking on wet surfaces and superb handling in the dry realizing an unmatched ride that could not be felt through any other SUV tires.



Net	
ning	

_	N FERARU1
	Competitor A
	Competitor B
	Conventional

- * Test Size : 255/55R18 109W
- * Test Site : Spain Idiada Applus P/G
 - STL (Standards Testing Labs, USA)
 - LPG (Laredo Providing Grounds. Ltd, USA)
 - TUV (TUV SUD Automotive, Germany)
- * Test vehicle : Volkswagen Touareg